



Part Code	A nominal mm (inch)	B mm (inch)	C mm (inch)	D min mm (inch)	Grip Range mm (inch) in 1-150mm (0.039 – 5.90)	Clamping Force Range N (lbf)	No of Cycles
0332-T2	2.20 (0.086)	Varies depending on grip range requested by customer.	Varies depending on grip range requested by customer.	7.00 (0.275)	1mm (0.039) to 150mm (5.905)	1,112(250) - 2,224 (500)	500
0432-T2	3.26 (0.128)			7.00 (0.275)	1mm (0.039) to 150mm (5.905)	1,779(400) - 3,558 (800)	500
0532-T2	3.96 (0.156)			7.00 (0.275)	1mm (0.039) to 150mm (5.905)	2,224(500) - 4,448 (1,000)	500
0632-T2	4.76 (0.188)			9.00 (0.354)	1mm (0.039) to 150mm (5.905)	2,670 (600) - 5,340 (1,200)	500
0832-T2	6.35 (0.250)			12.00 (0.472)	1mm (0.039) to 150mm (5.905)	2,670 (600) - 5,340 (1,200)	500
1032-T2	7.94 (0.313)			15.00 (0.590)	1mm (0.039) to 150mm (5.905)	4,000 (900) - 8,000 (1,800)	500
1232-T2	9.53 (0.375)			19.00 (0.748)	1mm (0.039) to 150mm (5.905)	4,000 (900) - 8,000 (1,800)	500
1432-T2	11.15 (0.438)			22.00 (0.866)	1mm (0.039) to 150mm (5.905)	5,250 (1,180) - 10,500 (2,360)	500
1632-T2	12.70 (0.500)			24.00 (0.945)	1mm (0.039) to 150mm (5.905)	5,250 (1,180) - 10,500 (2,360)	500
1832-L9	14.24 (0.563)			27.00 (1.063)	1mm (0.039) to 150mm (5.905)	6,250 (1,400) - 12,500 (2,800)	500
2032-L9	15.90 (0.625)			30.00 (1.181)	1mm (0.039) to 150mm (5.905)	7,250 (1,630) - 14,500 (3,260)	500
2432-L9	19.05 (0.750)			38.00 (1.496)	1mm (0.039) to 150mm (5.905)	7,250 (1,630) - 14,500 (3,260)	500
3232-L9	25.40 (1.000)			48.00 (1.889)	1mm (0.039) to 150mm (5.905)	8,000 (1,800) - 16,000 (3,600)	500

Head Types | FP = Flat Protruding | SP = Countersunk Protruding Grip Length Increments | 1-150mm



XX-0632A-XXX-XXX-SXT1

Kwikbolt Part Numbering

- Basic Part Number
- Grip Range
- Nominal Hole Diameter
- Head Configuration: SP –Countersunk Protruding
FP –Flat Protruding

Colour coding to customer specifications. Other loads, tolerances and diameters available to customer requirements

E-Mail: info@kwikbolt.com Web: www.kwikbolt.com Phone: +44 (0) 23 8220 5775